


SLBO-C



SLBO-C\_TDS\_V2-1/11/2017 \*Allergene list 07/12/2015

## Air lubrication and belt oil

The Frontmatec SLBO-C is a food grade NSF-H1 registered, high-quality, adhesive, lubrication oil intended for application in the food and drink industry for temperatures from -15°C and up to +120°C. Adhesive oil for air lube and belt chains.

The Frontmatec SLBO-C is highly resistant to aging and free from resinification. The SLBO-C can be used in locations in which there is a potential exposure of the lubricated part to food, and it offers a good protection against corrosion and is well compatible with plastics and sealings.

SLBO-E is compatible with mineral oils and is specifically designed for various belt chains, where it penetrates into the chains' inner surfaces. At the same time, it is formulated to refrain from dripping down from the chains. SLBO-C is also recommended for pneumatic systems and Marton air cylinders operating in room temperatures from +10°C to +50°C.

### Specifications

Chemical composition	Pharmaceutical and medical quality hydro-carbons registered according to NSF-H1, plus additives. All NSF-H1 registered.
NSF H1 Reg. number	150974
Density (+25°C/+77°F)	0.85 g/cm <sup>3</sup> (+/- 0.01)
Appearance	Clear, bright
Operating temperature	-15°C to +120°C/-5°F to +248°F
Viscosity index	Approx. 100
Refractive index	1,470-1,475
Package	5 l/cans, 20 l/cans or 200 l/barrel 1.32 gal/cans, 5.28 gal/cans or 52.83 gal/barrel

Technical changes are subject to alterations!

### Contact

Kolding, Denmark  
E-mail: [dkkol.aftersales@frontmatec.com](mailto:dkkol.aftersales@frontmatec.com)  
[frontmatec.com](http://frontmatec.com)