

SLBG-L-LT



SLBG-L-LT_TDS_V2-1/11/2017 *Allergene list: 07/12/2015

Low temperature grease for chill- and freezing tunnels

The Frontmatec SLBG-L-LT is a food grade NSF-H1 registered, high-quality, lubrication grease for bearings, low friction and low temperatures. Specially formulated for roller- and plain bearings in chill- and freezing tunnels.

The Frontmatec SLBG-L-LT is a grease with superior lubricating properties, extremely high water resistance properties and has particularly low friction values in freezing tunnels; also on plastic gear wheels and on different applications in slaughter houses. Therefore, this SLBG-L-LT grease provides great protection against wear and corrosion. SLBG-L-LT can be used both for material parts made from metal and plastic. This includes the Green Non-Fric plastics, where SLBG-L-LT would be the ideal grease if needed.

Specifications

Chemical composition	Synthetic oils, solid lubricants, active substances. All NSF-H1 registered.
NSF H1 Reg. number	150899
Appearance	White, soft
Operating temperature	-40°C to +140°C/+40°F to +284°F
Walk penetration	315 1/10mm (+/- 15) DIN ISO 2137
Oil separation	< 4 % (K) DIN 51 817
Package	400 g cartridges (with 25 pcs/case) 18 kg or 50 kg container 0.88 lb cartridges (with 25 pcs/case) 40 lb or 110 lb container

Technical changes are subject to alterations.

Contact

Kolding, Denmark
E-mail: dkkol.aftersales@frontmatec.com
frontmatec.com